

# BEAD BALANCE

## FOR TYRES

### APPLICATION CHART

#### HOW TO INSTALL BEAD BALANCE

1. Check the quantity chart for the proper amount of beads.
2. Mount bottom tyre bead and place inner pouch in the tyre.
3. Complete tyre mounting and install the provided metal sealing cap.

**BB12** = 12 oz (360 g)

**BB10** = 10 oz (300 g)

**BB8** = 8 oz (240 g)

**BB6** = 6 oz (180 g)

**BB4** = 4 oz (120 g)

Light Truck 16" to 18"  
Rated C or LT

235/65	R 16	BB4
305/65	R 16	BB6
345/65	R 16	BB8
235/75	R 16	BB4
245/75	R 16	BB4
265/75	R 16	BB4
285/75	R 16	BB6
295/75	R 16	BB6
315/75	R 16	BB8
225/85	R 16	BB4
235/85	R 16	BB4
245/85	R 16	BB4
255/85	R 16	BB6
265/85	R 16	BB6
305/85	R 16	BB8
245/70	R 17	BB4
265/70	R 17	BB4
275/70	R 17	BB4
285/70	R 17	BB6
315/70	R 17	BB6
245/75	R 17	BB4
235/80	R 17	BB4
275/65	R 18	BB6
245/70	R 18	BB6

# Medium & Heavy Duty Truck Sizes

8	R 17.5	BB4
8.5	R 17.5	BB4
9	R 17.5	BB6
9.5	R 17.5	BB6
10	R 17.5	BB8
205/65	R 17.5	BB4
245/70	R 17.5	BB4
265/70	R 17.5	BB6
315/70	R 17.5	BB8
215/75	R 17.5	BB4
225/75	R 17.5	BB4
235/75	R 17.5	BB6
245/75	R 17.5	BB6
315/80	R 17.5	BB10
445/45	R 19.5	BB12
435/50	R 19.5	BB12
265/55	R 19.5	BB8
385/55	R 19.5	BB12
425/55	R 19.5	BB12 + BB4
255/60	R 19.5	BB6
385/65	R 19.5	BB12
445/65	R 19.5	BB10 + BB4
225/70	R 19.5	BB6
245/70	R 19.5	BB6
265/70	R 19.5	BB6
285/70	R 19.5	BB8
295/70	R 19.5	BB8
305/70	R 19.5	BB10
315/70	R 19.5	BB10
8.25	R 20	BB8
9.0	R 20	BB10
10.00	R 20	BB10
11.00	R 20	BB12
12.00	R 20	BB12
14.00	R 20	BB12 + BB4
16.00	R 20	BB12 + BB6
405/70	R 20	BB12 + BB4
375/75	R 20	BB12 + BB4
425/75	R 20	BB12 + BB6
335/80	R 20	BB12

365/80	R 20	BB12
395/85	R 20	BB12 +BB6
24	R 20.5	BB12 +BB6
10	R 22.5	BB10
11	R 22.5	BB10
12	R 22.5	BB12
13	R 22.5	BB12
445/40	R 22.5	BB10 +BB4
455/40	R 22.5	BB10 +BB4
315/45	R 22.5	BB10
435/45	R 22.5	BB10 +BB4
445/45	R 22.5	BB10 +BB4
455/45	R 22.5	BB10 +BB4
495/45	R 22.5	BB12 +BB6
355/50	R 22.5	BB12
375/50	R 22.5	BB12
435/50	R 22.5	BB12 + BB4
445/50	R 22.5	BB12 + BB4
455/50	R 22.5	BB12 + BB4
295/55	R 22.5	BB10
385/55	R 22.5	BB12
295/60	R 22.5	BB10
315/60	R 22.5	BB10
385/65	R 22.5	BB12+ BB4
425/65	R 22.5	BB12 +BB6
445/65	R 22.5	BB12 +BB6
255/70	R 22.5	BB8
275/70	R 22.5	BB10
305/70	R 22.5	BB10
315/70	R 22.5	BB10
365/70	R 22.5	BB10 +BB4
445/75	R 22.5	BB10 + BB10
255/80	R 22.5	BB8
275/80	R 22.5	BB10
295/80	R 22.5	BB12
315/80	R 22.5	BB12
375/90	R 22.5	BB12 +BB6
12.00	R 24	BB12
325/95	R 24	BB10 +BB4
11	R 24.5	BB12 +BB6